

ENSTO

Fuse

FPT-FH.2A

Code	FPT-FH.2A
GTIN	6438100363734
Name	Fuse Ensto Vulcano Fuse-element, 2A for fireboxes
Description	If a fire short-circuits a device in a branch of a fire-resistant circuit, it may paralyze the entire circuit. This can be avoided by adding a fuse element to the fire protection junction box to separate the device from the main line. The fuse element containing a 2A fuse is supplied installed inside an M25 cable gland, and it is to be placed outside the junction box. This way, it does not take up wiring space inside the box. The fuse element contains two 1.5mm ² wires, the length 200 mm.



Vendor

Technical specification

Colors

Color: Black

Dimensions

Net Weight: 0.0331 kg

Conductor cross-section: 1,5 mm²

Electrical values

Nominal current A: 2 A

Nominal insulation voltage: 250 V

Pollution degree: 3

Ratings

Degree of protection: IP67

Flammability rating: V0

Others

ETIM Class: EC000036

ETIM 7 Technical specification

etim

Connection type: Other
Mounting method: Other
Type of current: AC
Rated current: 2 A
Rated voltage: 250 V
Dimensions glass fuse: 5x20 mm

Packaging

Pallet package

Unit: pcs
Package size: 3150
Depth: 1200 mm
Width: 800 mm
Height: 1067 mm

Default package

Unit: pcs
Package size: 50
Depth: 383 mm
Width: 258 mm
Height: 131 mm
Weight: 2.024 kg
Volume: 12.944634 l